

APPLICANT(S): BEN-DAVID, Ilan et al.
SERIAL NO.: Not yet assigned
FILED: Herewith
Page 3

AMENDMENTS TO THE CLAIMS

Please add or amend the claims to read as follows, and cancel without prejudice or disclaimer to resubmission in a divisional or continuation application claims indicated as cancelled:

1. **(Currently amended)** A color display device for displaying a more-than-three ~~primary~~ color image, the device comprising a driver control module to controllably activate one or more drivers of an array of sub-pixel elements of at least four ~~primary~~ different colors based on image data representing pixels of said color image in terms of at least three ~~primary colors~~ data components.
2. **(Original)** The device of claim 1, wherein said driver control module is able to generate one or more driver signals for activating said drivers based on one or more display attributes related to said display device and one or more image attributes related to said color image.
3. **(Currently amended)** The device of claim 2, wherein said driver control module comprises:
 - a conversion module ~~for to~~ converting said the image data representing pixels of said color image in terms of at least three data components into converted sub-pixel data representing said color image in terms of four or more ~~primary~~ colors; and
 - a controller to control said conversion module to convert said image data based on said one or more display-attributes and said one or more image-attributes.
4. **(Currently amended)** The device of claim 3, wherein said conversion module comprises:
 - a first converter ~~for to~~ converting said the image data representing pixels of said color image in terms of at least three data components into intermediate sub-pixel data of said four or more ~~primary~~ colors; and

a second converter ~~for~~ to converting said intermediate sub-pixel data into said converted sub-pixel data, based on at least one of said display attributes and said image attributes.

5. **(Currently amended)** The device of claim 4, wherein said second converter is able to convert said intermediate sub-pixel data using at least one conversion matrix, which is based on at least one of said display attributes and said image attributes.

6. **(Currently amended)** The device of claim 3, wherein said conversion module comprises:

a first converter ~~for~~ to converting said the image data representing pixels of said color image in terms of at least three data components into first intermediate sub-pixel data of said four or more ~~primary~~ colors;

a second converter ~~for~~ to converting said the image data representing pixels of said color image in terms of at least three data components into second intermediate sub-pixel data of three or more ~~primary~~ colors; and

a combiner to combine said first and second intermediate sub-pixel data into said converted sub-pixel data,

wherein said controller is able to control at least one of said first and second converters and said combiner based on at least one of said display attributes and image attributes.

7. **(Currently amended)** The device of claim 6, wherein said second converter is able to convert said the image data representing pixels of said color image in terms of at least three data components using at least one conversion matrix, which is based on at least one of said display attributes and said image attributes.

8. **(Currently amended)** The device of claim 5 ~~or~~ 7, wherein said controller is able to determine one or more values of said conversion matrix based on a

APPLICANT(S): BEN-DAVID, Ilan et al.
SERIAL NO.: Not yet assigned
FILED: Herewith
Page 5

combination of said one or more display-attributes and said one or more image-attributes.

9. **(Currently amended)** The device of ~~any one of claims 5, 7 and 8~~, wherein said controller is able to determine one or more values of said conversion matrix based on one or more timing signals related to said image data.
10. **(Currently amended)** The device of ~~any one of claims 3-9~~, wherein said driver control module comprises a sub-pixel processor to process said converted sub-pixel data, wherein said controller is able to control said processor to generate a sub-pixel signal based on at least one of said image attributes and said display attributes.
11. **(Currently amended)** The device of claim 10 comprising an interface module ~~for to generating~~ generate said driver signals based on said sub-pixel data signal.
12. **(Currently amended)** The device of ~~any one of claims 2-11~~ comprising a memory to store display-related data representing said one or more display attributes.
13. **(Currently amended)** The device of ~~any one of claims 2-12~~, wherein said one or more display-attributes comprise at least one attribute selected from the group consisting of a configuration of said sub-pixel elements within said array, a configuration of one or more defective sub-pixel elements within said array, a brightness non-homogeneity of said display device, and a color non-homogeneity of said display device.
14. **(Currently amended)** The device of ~~any one of claims 2-13~~, wherein said one or more image-attributes comprise one or more attributes selected from the group consisting of a perceived bit-depth of pixels of at least part of said image, a viewed smoothness of at least part of said image, a brightness uniformity of at least part of said image, a color uniformity of at least part of said image, and a rendering scheme to be applied to at least part of said image.

APPLICANT(S): BEN-DAVID, Ilan et al.
SERIAL NO.: Not yet assigned
FILED: Herewith
Page 6

15. **(Currently amended)** The device of ~~any one of the preceding~~ claims ~~1~~, comprising a display panel containing said driver control module and said array of sub-pixel elements.
16. **(Currently amended)** The device of ~~any one of the preceding~~ claims ~~1~~, wherein said array of sub-pixel elements comprises an array of liquid crystal elements.
17. **(Currently amended)** A method of displaying a more-than-three ~~primary~~ color image comprising controllably activating one or more drivers of an array of sub-pixel elements of at least four ~~primary~~ different colors, based on image data representing pixels of said color image in terms of at least three ~~primary~~ colors data components.
18. **(Currently amended)** The method of claim 17 comprising generating one or more driver signals for activating said drivers based on one or more ~~predetermined~~ display attributes related to said display device and one or more image attributes related to said color image.
19. **(Currently amended)** The method of claim 18, comprising converting said the image data representing pixels of said color image in terms of at least three data components into converted sub-pixel data representing said color image in terms of said at least four ~~primary~~ colors.
20. **(Currently amended)** The method of claim 19, wherein converting said the image data representing pixels of said color image in terms of at least three data components comprises:

converting said the image data representing pixels of said color image in terms of at least three data components into intermediate sub-pixel data of said at least four ~~primary~~ colors; and

converting said intermediate sub-pixel data into said converted sub-pixel data, based on at least one of said display attributes and image attributes.

21. **(Currently amended)** The method of claim 20, wherein converting said intermediate sub-pixel data comprises converting said intermediate sub-pixel data using at least one conversion matrix, which is based on at least one of said display attributes and said image attributes.
22. **(Currently amended)** The method of claim 19, wherein converting said image data comprises:
- converting said the image data representing pixels of said color image in terms of at least three data components into first intermediate sub-pixel data of said at least four primary colors;
 - converting said the image data representing pixels of said color image in terms of at least three data components into second intermediate sub-pixel data of at least three primary colors;
 - combining said first and second intermediate sub-pixel data into said converted sub-pixel data; and
 - controlling at least one of converting said image data into said first intermediate sub-pixel data, converting said image data into said second intermediate sub-pixel data, and said combining, based on at least one of said display attributes and said image attributes.
23. **(Currently amended)** The method of claim 22, wherein converting said image data into said second intermediate sub-pixel data comprises converting said image data using at least one conversion matrix, which is based on at least one of said display attributes and said image attributes.
24. **(Currently amended)** The method of claim 21 ~~or 23~~ comprising determining one or more values of said conversion matrix based on a combination of said one or more display-attributes and said one or more image-attributes.
25. **(Currently amended)** The method of ~~any one of claims 21, 23 and 24~~ comprising determining one or more values of said conversion matrix based on one or more timing signals related to said image data.

APPLICANT(S): BEN-DAVID, Ilan et al.
SERIAL NO.: Not yet assigned
FILED: Herewith
Page 8

26. **(Currently amended)** The method of ~~any one of~~ claims 19-25 comprising processing said converted sub-pixel data and generating a sub-pixel signal based on at least one of said image attributes and said display attributes.
27. **(Original)** The method of claim 26 comprising generating said driver signals based on said sub-pixel data signal.
28. **(Currently amended)** The method of ~~any one of~~ claims 18-27, wherein said one or more display-attributes comprise at least one attribute selected from the group consisting of a configuration of said sub-pixel elements within said array, a configuration of one or more defective sub-pixel elements within said array, a brightness non-homogeneity of said display device, and a color non-homogeneity of said display device.
29. **(Currently amended)** The method of ~~any one of~~ claims 18-28, wherein said one or more image-attributes comprise one or more attributes selected from the group consisting of a perceived bit-depth of pixels of at least part of said image, a viewed smoothness of at least part of said image, a brightness uniformity of at least part of said image, a color uniformity of at least part of said image, and a rendering scheme to be applied to at least part of said image.
30. **(Currently amended)** A color display system for displaying a more-than-three ~~primary~~ color image, the system comprising:
- an input interface for ~~to generating~~ generate image data signals representing pixels of said color image in terms of at least three ~~primary colors-data components~~; and
 - a driver control module to controllably activate one or more drivers of an array of sub-pixel elements of at least four ~~primary~~ different colors, based on said image data signals.
31. **(Original)** The system of claim 30, wherein said driver control module is able to generate one or more driver signals for activating said drivers based on one

APPLICANT(S): BEN-DAVID, Ilan et al.
SERIAL NO.: Not yet assigned
FILED: Herewith
Page 9

or more display attributes related to said display device and one or more image attributes related to said color image.

32. **(Currently amended)** The system of claim 31, wherein said driver control module comprises:

a conversion module ~~for~~ to converting said image data signals into converted sub-pixel data signals representing said color image in terms of four or more ~~primary~~ colors; and

a controller to control said conversion module to convert said image data signals based on said one or more display-attributes and said one or more image-attributes.

33. **(Canceled)**

34. **(Canceled)**

35. **(Canceled)**

36. **(Currently amended)** The system of ~~any one of~~ claims 32-35, wherein said driver control module comprises a sub-pixel processor to process said converted sub-pixel data signals, wherein said controller is able to control said processor to generate a sub-pixel signal based on at least one of said image attributes and said display attributes.

37. **(Canceled)**

38. **(Currently amended)** The system of ~~any one of~~ claims 30-37, wherein said one or more display-attributes comprise at least one attribute selected from the group consisting of a configuration of said sub-pixel elements within said array, a configuration of one or more defective sub-pixel elements within said array, a brightness non-homogeneity of said display device, and a color non-homogeneity of said display device.

39. **(Currently amended)** The system of ~~any one of~~ claims 30-38, wherein said one or more image-attributes comprise one or more attributes selected from the group consisting of a perceived bit-depth of pixels of at least part of said

APPLICANT(S): BEN-DAVID, Ilan et al.

SERIAL NO.: Not yet assigned

FILED: Herewith

Page 10

image, a viewed smoothness of at least part of said image, a brightness uniformity of at least part of said image, a color uniformity of at least part of said image, and a rendering scheme to be applied to at least part of said image.

40. **(Currently amended)** The system of ~~any one of~~ claims 30-39, comprising a display panel containing said driver control module and said array of sub-pixel elements.